

AD-A048 928

AEROSPACE MEDICAL RESEARCH LAB WRIGHT-PATTERSON AFB OHIO F/G 20/1
USAF BIOENVIRONMENTAL NOISE DATA HANDBOOK. VOLUME 81. F111-A AI--ETC(U)
FEB 77 J N COLE, J F ROSE


UNCLASSIFIED

AMRL-TR-75-50-VOL-81

NL

| 9 |

ADAD48 928



END
DATE
FILMED
2 -78
DDC

AD A 0 48928

14
AMRL-TR-75-50 -VOL-81
Volume 81

2
NW



9
Technical rept.

6
USAF BIOENVIRONMENTAL NOISE DATA HANDBOOK .

Volume 81 .

F111-A Aircraft, Near and Far-Field Noise .


10
Joh N. / Cole
Justus F. / Rose

11
FEB 1977

12 86p.

16 7231

17 04



Approved for public release; distribution unlimited.

AEROSPACE MEDICAL RESEARCH LABORATORY
AEROSPACE MEDICAL DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433

009 850

mt

NOTICES

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Please do not request copies of this report from Aerospace Medical Research Laboratory. Additional copies may be purchased from:

National Technical Information Service
5285 Port Royal Road
Springfield, Virginia 22161

Federal Government agencies and their contractors registered with Defense Documentation Center should direct requests for copies of this report to:


Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314

TECHNICAL REVIEW AND APPROVAL

This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER




HENNING E. VON GIERKE
Director

Biodynamics and Bionics Division
Aerospace Medical Research Laboratory

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AMRL-TR-75-50, Vol. 81	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) USAF BIOENVIRONMENTAL NOISE DATA HANDBOOK: F-111A Aircraft, Near and Far-Field Noise	5. TYPE OF REPORT & PERIOD COVERED Volume 81 of a series	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) John N. Cole Col Justus F. Rose	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Aerospace Medical Research Laboratory Aerospace Medical Division, Air Force Systems Command, Wright-Patterson AFB, OH 45433	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 7231-04-33 62202F 7231-04-36	
11. CONTROLLING OFFICE NAME AND ADDRESS Same as above	12. REPORT DATE February 1977	
	13. NUMBER OF PAGES 86	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) Unclassified	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Noise Noise Environments Bioenvironmental Noise Aircraft F-111A Aircraft		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The USAF F-111A is a tactical fighter aircraft powered by two TF30-P-1 turbofan engines. This report provides measured and extrapolated data defining the bioacoustic environments produced by this aircraft operating on a concrete runway pad for three engine/power conditions. Near-field data are reported for 4 locations in a wide variety of physical and psychoacoustic measures: overall and band sound pressure levels, C-weighted and A-weighted sound levels, preferred speech interference level, perceived noise level, and limiting times for		



DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

total daily exposure of personnel with and without standard Air Force ear protectors. Far-field data measured at 11 locations are normalized to standard meteorological conditions and extrapolated from 75-8000 meters to derive sets of equal-value contours for these same seven acoustic measures as functions of angle and distance from the source. Refer to Volume 1 of this handbook, USAF Bioenvironmental Noise Data Handbook, Vol 1: Organization, Content and Application, AMRL-TR-75-50(1) 1975, for discussion of the objective and design of the handbook, the types of data presented, measurement procedures, instrumentation, data processing, definitions of quantities, symbols, equations, applications, limitations, etc.

PREFACE

This report was prepared by the Biodynamic Environment Branch, Aerospace Medical Research Laboratory, under Project/Task 723104, Measurement and Prediction of Noise Environments of Air Force Operations.

The authors gratefully acknowledge Mr. Robert G. Powell for his assistance in preparing this report, Mr. Keith Kettler, Mr. Henry Mohlman and Mr. David Eilerman of the University of Dayton for assistance in the mechanics of data processing, and Mrs. Norma Peachey and Mr. Mike Patterson for assistance in typing and preparation of the graphics.

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
IS	SPECIAL
<div style="font-size: 2em; font-family: cursive; position: absolute; left: 10px; bottom: 10px;">A</div>	

Table of Contents

	<i>Page</i>
INTRODUCTION	3
NEAR-FIELD NOISE	4
FAR-FIELD NOISE	6

List of Tables

NEAR-FIELD NOISE	
1. Measurement Locations and Test Conditions	5
2. Measured Sound Pressure Level, Octave Band	8
3. Measures of Human Noise Exposure	9
FAR-FIELD NOISE	
4. Test Conditions	10
5. Measured Sound Pressure Level	11-13
6. Directivity Index	20-22

List of Figures

NEAR-FIELD NOISE	
1. Measurement Locations	5
FAR-FIELD NOISE	
2. Measurement Locations	7
3. Normalized Far-Field Noise Levels	14-16
4. Acoustic Power Level	17-19
5. Overall Sound Pressure Level — Contours	23-25
6. C-Weighted Sound Level — Contours	26-28
7. A-Weighted Sound Level — Contours	29-31
8. Perceived Noise Level — Contours	32-34
9. Speech Interference Level — Contours	35-37
10. Permissible Exposure Time — Contours	38-55
11. Octave Band Sound Pressure Level — Contours	56-82

INTRODUCTION

The USAF F-111A is a tactical fighter-type aircraft powered by two TF30-P-1 turbofan engines. The aircraft was manufactured by the General Dynamics and the engines by Pratt and Whitney, a Division of United Aircraft.

This volume provides measured and extrapolated data defining bioacoustic environments produced by this aircraft during ground runup operations. Such data are essential to evaluate ear protection requirements, limiting personnel exposure times, voice communication capabilities, and annoyance problems associated with ground runups of the F-111A aircraft. These measured data were also published (reference 1) in 1968 in another format.

This volume is one of a series published by the AMRL under the same report number (AMRL-TR-75-50) as a multi-volume handbook that quantifies the noise environments produced at flight/ground crew locations and in surrounding communities by operations of Air Force aircraft and ground support equipment. The far-field, community-type, noise data in the handbook describe the noise produced during *ground operations* of aircraft, ground support equipment, and other ground-based equipment or facilities.

Volume 1 of this handbook discusses the objectives and design of the handbook, the types of data presented, measurement procedures, instrumentation, data processing, definitions of quantities, symbols, equations, applications, limitations, etc. Volume 2 provides a method and data for adjusting the handbook's far-field noise data, which are for standard meteorological conditions (15°C temperature, 70% rel humidity, 0.760 meters Hg barometric pressure), to derive comparable data for other meteorological conditions. *Refer to Volumes 1 and 2* (references 2 and 3) for such information because it is not repeated in other handbook volumes.

A cumulative index lists those aerospace systems contained in the handbook, and identifies the specific volumes containing each type of environmental noise data available (i.e., inflight/flight crew and passenger noise, near-field/ground crew noise, far-field/community noise). Volume numbers are assigned sequentially as individual volumes are published. This index is periodically updated as individual volumes are published and is available upon request from AMRL/BBE, Wright-Patterson AFB, OH 45433. Organizations on the distribution list for the handbook will automatically receive a copy of each updated index.

Direct any questions concerning the technical data in this report and other handbook volumes to: AMRL/BBE, Wright-Patterson AFB, OH 45433; AUTOVON 78-53675 or 78-53664; Commercial (513) 255-3675 or (513) 255-3664.

-
1. Cole, John N., J. F. Rose, Jr., Maj., *Acoustic Environments of the F-111A Aircraft During Ground Runup*, AMRL-TR-68-14, Aerospace Medical Research Laboratory, Wright-Patterson AFB, Ohio, 1968.
 2. Cole, John N., *USAF Bioenvironmental Noise Data Handbook Volume 1: Organization, Content and Application*, AMRL-TR-75-50 (1), Aerospace Medical Research Laboratory, Wright-Patterson Air Force Base, Ohio, 1975.
 3. Cole, John N., *USAF Bioenvironmental Noise Data Handbook, Volume 2: Procedure to Evaluate Effects of Non-standard Meteorological Conditions on Far-Field Noise*, AMRL-TR-75-50 (2), AMRL, WPAFB, OH, 1975.

NEAR-FIELD NOISE

MEASUREMENTS

AMRL acquired near-field noise data on the F-111A aircraft during ground runup operations of its turbofan engines. For these tests the aircraft was located on a concrete runup pad at Wright-Patterson AFB with no significant reflecting surfaces in the vicinity except the ground plane. Table 1 gives the surface meteorological conditions and the engines' power conditions. The ground-crew chief selected power conditions and near-field locations generally used during routine maintenance or engine runup for preflight checks.

At each near-field location a test engineer randomly moved a hand-held microphone in and around each location, probing all areas where a crew member's head would normally be located. He recorded all the noise samples on magnetic tape. During analysis of each sample, he determined the octave band root-mean-square sound pressure to derive a power-averaged level for each location. Figure 1 shows the four near-field locations where ground crews are usually located for maintenance and/or preflight checkout operations. Estimates of noise levels at other locations are difficult in the near-field since the noise source is spatially distributed, i.e., not a point source. The noise levels at near-field locations can vary widely depending upon relative distances from each noise source (intake noise, exhaust noise, panel resonances, internal engine noise through the engine wall, etc.).

Table 1 lists the numeric/alphabetic designators used on the data pages in this report to identify the measurement locations and test conditions. For example, the designator 1/A means ground crew location 1 and test condition A.

RESULTS

The measured data presented in Table 2 define the sound pressure levels (SPL) produced by the F-111A aircraft at the four ground crew locations. This table includes the overall, 1/3 octave band, and octave band levels. From these data one can calculate the variety of measures given in Table 3, which are widely used to assess the effects of noise on personnel and their performance.

All near-field data are for the meteorological conditions at the time of test but are valid for all typical airbase meteorology because of the short sound propagation distances involved.

TABLE 1
MEASUREMENT LOCATIONS AND TEST CONDITIONS
FOR NEAR-FIELD NOISE MEASUREMENTS

F-111A Aircraft, Ground Runup, Wright-Patterson AFB
29 August 1967
Tail # 63-9775

Ground Crew Location


1	Engine Start
2	Wheel Chock Pull
3	Engine Trimming
4	Marshal

Aircraft Engine Operation

A	Engine #1 at 85% RPM Engine #2 at Idle
---	---

Meteorology

Temperature	21 °C
Bar Pressure	0.767 M Hg
Rel Humidity	55 %
Wind — Speed	1.5 M/Sec (3 kt)
— Direction	260 Deg.



**Figure 1. Near-Field Measurement Locations on Runup
Pad at Wright-Patterson AFB OH**

FAR-FIELD NOISE

MEASUREMENTS

AMRL acquired the near- and far-field data during a 1- 2-hour test period, thus keeping similar meteorological conditions. Figure 2 shows the aircraft, on a concrete runup pad, the ground cover and aircraft orientation relative to 11 microphone measurement sites on a semicircle. The center of the 76 meter radius semicircle used in surveying the TF30-P-1 engines was on the ground directly below the intersection of the aircraft's centerline and the plane passing through the engines' nozzle exits. The ground runup pad did not have a blast deflector; therefore, the engines' exhausts were in a "free-flow" condition.

Table 4 provides cockpit readouts of engines in operation for each far-field test. Also listed in this table are the surface meteorological conditions during data acquisition.

All 11 microphone measurement sites are in the acoustic far-field of the source where the sound wave-fronts spherically diverge and the noise source may be regarded as a point source.

A portable microphone/tape recorder system was used to sequentially record the noise at each far-field location. The microphone was hand-held 1.8 meters (6 feet) above the ground and pointed at the source (0° angle of incidence).

RESULTS

Table 5 lists the overall and octave band SPL measured and estimated* at the far-field locations under meteorological conditions at the time of the test. Data in all other figures and tables are based on these levels. These data were normalized to 100 meters distance and standard meteorological conditions (15°C temperature, 70% relative humidity, 0.760 meter Hg barometric pressure) and used to derive the graphic data in Figure 3 which provides a compact summary of the far-field noise characteristics of the F-111A aircraft in a standard format.

Figure 4 and Table 6 present two basic acoustic measures, the acoustic power levels and the directivity index, respectively. The acoustic power level describes the power radiated by the source as a function of frequency. The directivity index is a standard acoustical engineering measure that describes the geometric way in which the source radiates this power as a function of both frequency and angle from source. These basic source measures are primarily of interest for acoustical engineers and noise generation/control specialists.

*NOTE: The computer software program used to calculate some of the results presented in the handbook requires input data at 10-degree increments between starting and ending angles. As shown in Figure 2, six such measurement angles were not surveyed during this test. To fulfill software requirements estimated data were used at these angles. These estimated levels were derived by interpolating/extrapolating from octave band SPL data measured at the 11 angles and by considering directivity patterns typical for this type noise source.

Estimates of the noise levels for a different number of engines operating (e.g., two engines in A/B) can be determined as explained in Volume 1 of this handbook.

Figures 5 through 11 are sets of equal noise contours describing seven different measures of noise as a function of angle and distance from the source for standard day meteorology. They are, respectively, overall sound pressure level, C-weighted sound level, A-weighted sound level, perceived noise level, speech interference level, permissible exposure times for personnel and octave band sound pressure levels.

No data are presented beyond the 170 degree location because of turbulent air flow behind the aircraft. Typically, the A-weighted levels for the 180 angle are 5 to 15 dBA below the level at the 170 degree location.

Test personnel performed noise surveys during quiet periods when the background noise was minimal, e.g., early in the morning when no other aircraft or engine test stands were operating. Data eliminated because they were near the background/electronic noise were generally not significant because the levels were so low.

Volume 2 of the handbook describes the influence of meteorology on far-field noise environments, and provides, if required, the factors necessary to adjust the handbook's standard meteorological day data.




Figure 2. Far-Field Measurement Locations on Runup Pad at Wright-Patterson AFB OH

TABLE: MEASURED SOUND PRESSURE LEVEL (DB)		IDENTIFICATION:			
OCTAVE BAND					
2		OMEGA 3.2			
		TEST 73-002-001			
NOISE SOURCE/SUBJECT:		KUN 01			
F-111A AIRCRAFT		12 MAR 76			
GROUND CREW		PAGE F1			
NEAR FIELD NOISE LEVELS					
		- LOCATION/CONDITION			
FREQ (HZ)	1/A	2/A	3/A	4/A	
31.5	97	99	99	94	
63	110	111	110	101	
125	116	115	116	109	
250	122	117	118	112	
500	117	117	118	109	
1000	115	118	115	107	
2000	113	119	113	107	
4000	112	120	121	108	
8000	114	121	118	112	
OVERALL	125	127	126	118	
LEVEL CORRECTED TO REMOVE BACKGROUND/ELECTRONIC NOISE.					

TABLE: MEASURES OF HUMAN NOISE EXPOSURE					IDENTIFICATION:
3					
NOISE SOURCE/SUBJECT:	OPERATION:				OMEGA 3.2 TEST 73-002-001 KUN 01
F-111A AIRCRAFT	(
GROUND CREW	(12 MAR 76
NEAR FIELD NOISE LEVELS	(PAGE H1
LOCATION/CONDITION					
	1/A	2/A	3/A	4/A	
HAZARD/PROTECTION					
C-WEIGHTED OVERALL SOUND LEVEL (OASLC IN DB) AT EAR					
A-WEIGHTED OVERALL SOUND LEVEL (OASLA IN DB) AT EAR					
MAXIMUM PERMISSIBLE TIME (T IN MINUTES) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)					
NO PROTECTION					
OASLC	125	126	126	117	
OASLA	122	126	125	116	
T	P	P	P	P	
MINIMUM QPL EAR MUFFS					
OASLA*	101	101	101	94	
T	25	25	25	85	
AMERICAN OPTICAL 1700 EAR MUFFS					
OASLA*	97	97	96	89	
T	50	50	60	202	
V-51K EAR PLUGS					
OASLA*	97	99	98	90	
T	50	36	42	170	
AMERICAN OPTICAL 1700 EAR MUFFS PLUS V-51K EAR PLUGS					
OASLA*	83	85	83	76	
T	571	404	571	960	
H-133 GROUND COMMUNICATION UNIT					
OASLA*	93	97	94	87	
T	101	50	85	285	
COMMUNICATION					
PREFERRED SPEECH INTERFERENCE LEVEL (PSIL IN DB)					
PSIL	115	118	115	108	
ANNOYANCE					
PERCEIVED NOISE LEVEL (PNL IN PNDB)					
PNL	135	140	140	130	

* BASED ON CALCULATED SPL SPECTRUM UNDER PROTECTIVE DEVICE.
P ADDITIONAL EAR PROTECTION REQUIRED.

TABLE 4
TEST CONDITIONS
FOR FAR-FIELD NOISE MEASUREMENTS

F-111A Aircraft, Ground Runup
Wright-Patterson AFB, 29 August 1967
Tail # 63-9775

Aircraft Engine Operation

Military Power	Single Engine
Military Power	Both Engines
Afterburner Power	Single Engine

Meteorology

Temperature	21 °C
Bar Pressure	0.767 M Hg
Rel Humidity	55 %
Wind — Speed	1.5 M/Sec (3 Kt)
— Direction	260 Deg.

TABLE: MEASURED SOUND PRESSURE LEVEL (DB)																
OCTAVE BAND																
DISTANCE = 76 METERS																
NOISE SOURCE/SUBJECT: (OPERATION:) METEOROLOGY:) IDENTIFICATION:																
F-111A AIRCRAFT) TEMP = 21 C))																
TF30-P-1 ENGINE) MILITARY POWER) BAR PRESS = .767 M HG) OMEGA 1.4																
FAR FIELD NOISE) SINGLE ENGINE) REL HUMID = 55 %) TEST 75-002-036																
) FREE FLOW))) RUN 01																
)))) 07 MAY 75																
))))) PAGE 2																
FREQ																
ANGLE (DEGREES)																
0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180																
31.5																
63																
125																
250																
500																
1000																
2000																
4000																
8000																
OVERALL																
LEVEL CORRECTED TO REMOVE BACKGROUND/ELECTRONIC NOISE.																

LEVEL CORRECTED TO REMOVE BACKGROUND/ELECTRONIC NOISE.

TABLE: MEASURED SOUND PRESSURE LEVEL (DB)														IDENTIFICATION:	
5														OMEGA 1.4	
OCTAVE BAND														TEST 75-002-036	
DISTANCE = 76 METERS														RUN 02	
NOISE SOURCE/SUBJECT:														07 MAY 75	
(PAGE 2	
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(
(

TABLE: MEASURED SOUND PRESSURE LEVEL (DB)																	IDENTIFICATION:	
OCTAVE BAND																		
DISTANCE = 76 METERS																		
NOISE SOURCE/SUBJECT:																		
(OPERATION:																		
(
(MILITARY PLUS AFTERBURNER																		
(SINGLE ENGINE																		
(FREE FLOW																		
F-111A AIRCRAFT																		
TF30-P-1 ENGINE																		
FAR FIELD NOISE																		
FREQ (HZ)																		
ANGLE (DEGREES)																		
0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180																		
31.5	98	98	98	98	99	100	101	102	104	106	106	108	112	117	121	122	121	115
63	103	103	103	105	108	109	109	110	111	112	117	122	126	128	129	124	116	
125	101	105	107	107	107	107	108	109	111	116	123	127	129	130	124	114		
250	103	103	104	101	99	100	103	104	105	106	113	119	123	122	118	115	101	
500	100	101	103	104	105	107	109	111	113	114	119	126	128	122	114	109	95	
1000	99	101	104	105	106	108	110	112	114	116	120	123	123	118	113	107	95	
2000	99	100	101	102	104	105	107	109	112	113	117	118	117	112	105	100	94	
4000	97	98	100	101	103	104	105	107	109	110	113	113	111	105	100	97	91	
8000	96	97	98	99	99	99	99	99	101	103	104	106	106	104	100	95	92	86
OVERALL	110	111	112	113	114	115	117	118	120	121	126	131	133	133	133	128	120	
LEVEL CORRECTED TO REMOVE BACKGROUND/ELECTRONIC NOISE.																		

FIGURE 1 NORMALIZED FARFIELD NOISE LEVELS

3 DISTANCE = 100 METERS

NOISE SOURCE/SUBJECT:

F-111A AIRCRAFT
TF30-P-1 ENGINE
FAR FIELD NOISE

OPERATION:

MILITARY POWER
SINGLE ENGINE
FREE FLOW

METEOROLOGY:

TEMP = 15 C
BAR PRESS = .760 M HG
REL HUMID = 70 %

IDENTIFICATION:

OMEGA 1.4
TEST 75-002-036
RUN 01
07 MAY 75
PAGE 6





FIGURE 1 NORMALIZED FARFIELD NOISE LEVELS

3 DISTANCE = 100 METERS

NOISE SOURCE/SUBJECT

OPERATION

F-111A AIRCRAFT
TF30-P-1 ENGINE
FAR FIELD NOISE

MILITARY POWER
BOTH ENGINES
FREE FLOW

METEOROLOGY

TEMP = 15 C
BAR PRESS = .760 M HG
REL HUMID = 70 %

OMEGA 1.4

TEST 75-002-036

RUN 02

07 MAY 75

PAGE 6





FIGURE: NORMALIZED FARFIELD NOISE LEVELS

3 DISTANCE = 100 METERS

IDENTIFICATION:

OMEGA 1.4

TEST 75-002-036

RUN 03

07 MAY 75

PAGE 6

NOISE SOURCE/SUBJECT:

OPERATION:

MILITARY PLUS AFTERBURNER

SINGLE ENGINE

FREE FLOW

METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %





FIGURE: ACOUSTIC POWER LEVEL (PWL)

4

NOISE SOURCE/SUBJECT: F-111A AIRCRAFT
 TF30-P-1 ENGINE
 FAR FIELD NOISE

OPERATION: MILITARY POWER
 SINGLE ENGINE
 FREE FLOW

METEOROLOGY: TEMP = 21 C
 BAR PRESS = .767 M HG
 REL HUMID = 55 %

IDENTIFICATION: OMEGA 1.4
 TEST 75-002-036
 RUN 01
 07 MAY 75
 PAGE 3




FIGURE: ACOUSTIC POWER LEVEL (PWL)

4

NOISE SOURCE/SUBJECT: (OPERATION:) METEOROLOGY:)

F-111A AIRCRAFT (MILITARY POWER) TEMP = 21 C

TF30-P-1 ENGINE (BOTH ENGINES) BAR PRESS = .767 M HG

FAR FIELD NOISE (FREE FLOW) REL HUMID = 55 %

IDENTIFICATION:)

OMEGA 1.4

TEST 75-002-036

RUN 02

07 MAY 75

PAGE 3

PWL





TABLE: DIRECTIVITY INDEX (DB)																	IDENTIFICATION:		
6																	OMEGA 1.4		
NOISE SOURCE/SUBJECT:																	TEST 75-002-036		
(OPERATION:																	RUN 01		
(F-111A AIRCRAFT																	TEMP = 21 C		
(TF30-P-1 ENGINE																	BAR PRESS = .767 M HG		
(FAR FIELD NOISE																	REL HUMID = 55 %		
(FREE FLOW																	PAGE 4		
FREQ																	ANGLE (DEGREES)		
(HZ)	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
OCTAVE																			
31.5	-14	-14	-14	-14	-14	-13	-12	-10	-9	-8	-7	-6	-3	1	5	8	9	7	
63	-23	-20	-17	-15	-13	-13	-11	-12	-11	-10	-10	-8	-4	-0	5	9	10	4	
125	-18	-14	-12	-13	-13	-13	-13	-13	-12	-10	-8	-7	-3	1	5	9	10	-0	
250	-5	-5	-6	-8	-10	-9	-9	-7	-6	-5	-6	-5	-1	3	5	7	8	3	
500	-12	-11	-10	-10	-10	-9	-8	-7	-7	-6	-4	-2	1	4	6	6	5	-7	
1000	-11	-11	-10	-10	-10	-10	-9	-6	-5	-4	-1	0	2	5	5	4	1	-4	
2000	-6	-6	-6	-6	-6	-5	-5	-4	-3	-2	1	3	4	5	3	1	-2	-4	
4000	-3	-3	-2	-2	-2	-2	-3	-2	-2	-1	1	3	4	4	2	-1	-4	-5	
8000	-1	0	1	1	1	0	-1	-1	-1	0	-1	1	1	1	0	-1	-4	-4	
OVERALL	-11	-10	-10	-10	-10	-10	-9	-8	-8	-7	-5	-3	-1	3	5	8	8	1	


TABLE: DIRECTIVITY INDEX (DB)																
6																
NOISE SOURCE/SUBJECT:																
F-111A AIRCRAFT																
TF30-P-1 ENGINE																
FAR FIELD NOISE																
FREQ (HZ)																
OCTAVE																
ANGLE (DEGREES)																
IDENTIFICATION:																
OMEGA 1.4																
TEST 75-002-036																
RUN 02																
METEOROLOGY:																
TEMP = 21 C																
BAR PRESS = .767 M HG																
REL HUMID = 55 %																
PAGE 4																
FREQ (HZ)																
OCTAVE																
31.5																
63																
125																
250																
500																
1000																
2000																
4000																
8000																
OVERALL																

TABLE: DIRECTIVITY INDEX (DB)																
6																
NOISE SOURCE/SUBJECT:																
(OPERATION:																
F-111A AIRCRAFT																
TF30-P-1 ENGINE																
FAR FIELD NOISE																
FREQ																
(HZ)																
OCTAVE																
31.5																
63																
125																
250																
500																
1000																
2000																
4000																
8000																
OVERALL																
ANGLE (DEGREES)																
0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180																
-16 -16 -16 -16 -15 -14 -13 -12 -11 -9 -7 -6 -1 4 6 6 6 1 -7																
-18 -18 -18 -18 -17 -16 -15 -14 -13 -12 -11 -10 -8 -4 3 7 8 7 1																
-21 -17 -15 -15 -15 -15 -15 -14 -13 -11 -11 -10 -9 -4 5 7 8 3 -5																
-12 -12 -11 -14 -16 -15 -15 -12 -11 -10 -9 -8 -7 -2 4 8 7 3 -0 -14																
-20 -19 -17 -16 -15 -13 -12 -11 -9 -7 -5 -3 -1 3 6 8 2 -6 -11 -25																
-18 -16 -13 -12 -11 -9 -8 -6 -4 -1 0 4 5 6 1 -4 -10 -22																
-14 -13 -12 -11 -9 -8 -6 -4 -3 -1 1 2 5 5 4 -1 -8 -13 -19																
-11 -10 -8 -7 -5 -4 -3 -3 -1 -1 1 2 4 4 2 -2 -7 -10 -16																
-6 -5 -4 -3 -3 -3 -3 -3 -1 -1 1 2 4 4 2 -2 -7 -10 -16																
-17 -16 -15 -14 -13 -12 -11 -9 -7 -6 -1 4 6 6 6 1 -7																

FIGURE: OVERALL SOUND PRESSURE LEVEL {OASPL}
F
EQUAL LEVEL CONTOURS (DB)




POINT	DB
A	55
B	60
C	65
D	70
E	75
F	80
G	85
H	90
I	95
J	100
K	105
L	110
M	115
N	120
O	125
P	130




IDENTIFICATION: OMEGA 1.4
 TEST 75-002-036
 RUN 01
 07 MAY 75
 PAGE 14

METEOROLOGY:
 TEMP = 15 C
 BAR PRESS = .760 M HG
 REL HUMID = 70 %

NOISE SOURCE/SUBJECT: OPERATION:
 F-111A AIRCRAFT MILITARY POWER
 TF30-P-1 ENGINE SINGLE ENGINE
 FAR FIELD NOISE FREE FLOW



1



IDENTIFICATIONS:


OMEGA 1.6

1) METEOROLOGY:

TEMP = 15 C
BAR PRESS = .760 M HG
REL HUMID = 70 %

07 MAY 75

PAGE 14



(FIGURE: A-WEIGHTED OVERALL SOUND LEVEL (OASLA)
 (7
 (EQUAL LEVEL CONTOURS (DBA)
 (-----)
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (SINGLE ENGINE
 (FAR FIELD NOISE (FREE FLOW
 (-----)
 (METEOROLOGY: (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (-----)
 (IDENTIFICATION: (OMEGA 1.4
 (TEST 75-002-036
 (RUN 01
 (07 MAY 75
 (PAGE 15
 (-----)




FIGURE 7: A-WEIGHTED OVERALL SOUND LEVEL (OASLA) EQUAL LEVEL CONTOURS (DBA)

IDENTIFICATION:

OMEGA 1.4

TEST 75-002-036

RUN 02

•

07 MAY 70

1) METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %

OPERATION:

100

MILITARY POWER


BOTH ENGINES

NOISE SOURCE/SUBJECT:


1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
84

F-111A AIRCRAFT

TF30-P-1 ENGINE



(FIGURE: A-WEIGHTED OVERALL SOUND LEVEL (OASLA)
 (7 EQUAL LEVEL CONTOURS (DBA)
 (NOISE SOURCE/SUBJECT: (OPERATION: (METEOROLOGY: (IDENTIFICATIONS: ()
 (F-111A AIRCRAFT (MILITARY PLUS AFTERBURNER) TEMP = 15 C () OMEGA 1.4
 (TF30-P-1 ENGINE (SINGLE ENGINE) BAR PRESS = .760 M HG () TEST 75-002-036
 (FAR FIELD NOISE (FREE FLOW) REL HUMID = 70 % () RUN 03
 () 07 MAY 75
 () PAGE 15



ANGLE IN DEGREES



FIGURE: PERCEIVED NOISE LEVEL {PNL}	IDENTIFICATION:
8	
EQUAL LEVEL CONTOURS (PNDB)	
NOISE SOURCE/SUBJECT:	OMEGA 1.4
	TEST 75-002-036
	RUN 02
OPERATION:	METEOROLOGY:
	TEMP = 15 C
F-111A AIRCRAFT	BAR PRESS = .760 M HG
TF30-P-1 ENGINE	REL HUMID = 70 %
FAR FIELD NOISE	FREE FLOW
	PAGE 16


FIGURE: PERCEIVED NOISE LEVEL (PNL)
 8
 EQUAL LEVEL CONTOURS (PNDB)

IDENTIFICATION:
 OMEGA 1.4
 TEST 75-002-036
 RUN 03


NOISE SOURCE/SUBJECT: (OPERATION:)
 F-111A AIRCRAFT (MILITARY PLUS AFTERBURNER)
 TF30-P-1 ENGINE (SINGLE ENGINE)
 FAR FIELD NOISE (FREE FLOW)

METEOROLOGY:
 TEMP = 15 C
 BAR PRESS = .760 M HG
 REL HUMID = 70 %

07 MAY 75
 PAGE 16



((FIGURE: PREFERRED SPEECH INTERFERENCE LEVEL (PSIL)
 ((9 EQUAL LEVEL CONTOURS (DB)
 (() IDENTIFICATION:
 (() OMEGA 1.4
 (() TEST 75-002-036
 (() RUN 01
 (() METEOROLOGY:
 (() TEMP = 15 C
 (() BAR PRESS = .760 M HG
 (() REL HUMID = 70 %
 (() 07 MAY 75
 (() PAGE 17
 (()
 ((NOISE SOURCE/SUBJECT: (OPERATION:
 (()
 ((F-111A AIRCRAFT (MILITARY POWER
 ((TF30-P-1 ENGINE (SINGLE ENGINE
 ((FAR FIELD NOISE (FREE FLOW




IDENTIFICATION:


RUN 02
07 MAY 75
PAGE 17



FIGURE: 9
 PREFERRED SPEECH INTERFERENCE LEVEL (PSIL)
 EQUAL LEVEL CONTOURS (DB)
 IDENTIFICATION:
 OMEGA 1.4
 TEST 75-002-036
 RUN 03
 NOISE SOURCE/SUBJECT:
 (F-111A AIRCRAFT)
 (TF30-P-1 ENGINE)
 (FAR FIELD NOISE)
 OPERATION:
 (MILITARY PLUS AFTERBURNER)
 (SINGLE ENGINE)
 (FREE FLOW)
 METEOROLOGY:
 TEMP = 15 C
 BAR PRESS = .760 M HG
 REL HUMID = 70 %
 07 MAY 75
 PAGE 17



```
(-----)
( FIGURE: MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73) ) IDENTIFICATION:
( EQUAL TIME CONTOURS (MINUTES) ) )
( NO PROTECTION ) OMEGA 1.4
( TEST 75-082-036 )
( NOISE SOURCE/SUBJECT: ) METEOROLOGY: ) RUN 01
( F-111A AIRCRAFT ) TEMP = 15 C )
( TF30-P-1 ENGINE ) MILITARY POWER ) BAR PRESS = .760 M HG )
( FAR FIELD NOISE ) SINGLE ENGINE ) REL HUMID = 70 % )
( FREE FLOW ) ) PAGE 7
(-----)
```



P ADDITIONAL EAR PROTECTION REQUIRED.


```
(-----)
( FIGURE: MAXIMUM PERMISSIBLE TIME {T} FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73) ) IDENTIFICATION: )
( EQUAL TIME CONTOURS (MINUTES) ) )
(      10      ) ) OMEGA 1.4 )
( AMERICAN OPTICAL 1700 EAR MUFFS ) TEST 75-082-036 )
( NOISE SOURCE/SUBJECT: ) OPERATION: ) METEOROLOGY: ) RUN 01 )
( F-111A AIRCRAFT ) MILITARY POWER ) TEMP = 15 C ) )
( TF30-P-1 ENGINE ) SINGLE ENGINE ) BAR PRESS = .760 M HG ) )
( FAR FIELD NOISE ) FREE FLOW ) REL HUMID = 70 % ) )
( ) ) PAGE 9 )
(-----)
```




FIGURE: MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)

IDENTIFICATION:

10

EQUAL TIME CONTOURS (MINUTES)

V-51R EAR PLUGS

NOISE SOURCE/SUBJECT:

OPERATION:

METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %

F-111A AIRCRAFT

MILITARY POWER

TF30-P-1 ENGINE

SINGLE ENGINE

FAR FIELD NOISE

FREE FLOW

OMEGA 1.4

TEST 75-002-036

RUN 01

07 MAY 75

PAGE 10

POINT

MIN

A 960

B 480

C 240

D 120




FIGURE: MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)

IDENTIFICATION:

10 EQUAL TIME CONTOURS (MINUTES)

H-133 GROUND COMMUNICATION UNIT

NOISE SOURCE/SUBJECT:

OPERATION:

MILITARY POWER

SINGLE ENGINE

FREE FLOW

METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %

OMEGA 1.4

TEST 75-002-036

RUN 01

07 MAY 75

PAGE 12

POINT MIN

A 960

B 480

C 240




FIGURE: MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)

IDENTIFICATION:

10

NOISE SOURCE/SUBJECT:

OPERATION:

MILITARY POWER

BOTH ENGINES

FREE FLOW

METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %

OMEGA 1.4

TEST 75-002-036

RUN 02

07 MAY 75

PAGE 8






FIGURE	MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)	IDENTIFICATION
10	EQUAL TIME CONTOURS (MINUTES)	
	AMERICAN OPTICAL 1700 EAR MUFFS	OMEGA 1.4
		TEST 75-002-036
NOISE SOURCE/SUBJECT	OPERATION	METEOROLOGY
F-111A AIRCRAFT	MILITARY POWER	TEMP = 15 C
TF30-P-1 ENGINE	BOTH ENGINES	BAR PRESS = .760 M HG
FAR FIELD NOISE	FREE FLOW	REL HUMID = 70 %
		PAGE 9

The graph displays three curves representing different levels or depths, plotted on a grid. The x-axis is labeled "DISTANCE FROM SOURCE (METERS)" and ranges from 0 to 8. The y-axis is labeled "POINT" and ranges from 0 to 180. The curves are labeled 120, 480, and 1000, indicating different levels or depths. The curves are plotted with points A, B, C, D, and E marked at various distances.


Distance (meters)	Point 120	Point 480	Point 1000
0	A	A	A
1	B	B	B
2	C	C	C
3	D	D	D
4	E	E	E
5	A	A	A
6	B	B	B
7	C	C	C
8	D	D	D

[illegible]

	MIN		POINT	
0	(960	A)
	(480	B)
10	(C)
	(240	D)
20	(E)
	(120)
	(60)



FIGURE#	MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)	IDENTIFICATION:
10	EQUAL TIME CONTOURS (MINUTES)	
	H-133 GROUND COMMUNICATION UNIT	OMEGA 1.4
		TEST 75-002-036
NOISE SOURCE/SUBJECT#	OPERATION:	METEOROLOGY:
F-111A AIRCRAFT	MILITARY POWER	TEMP = 15 C
TF30-P-1 ENGINE	BOTH ENGINES	BAR PRESS = .760 M HG
FAR FIELD NOISE	FREE FLOW	REL HUMID = 70 %
		PAGE 12



[illegible]

FIGURE: MAXIMUM PERMISSIBLE TIME (T) FOR ONE EXPOSURE PER DAY (AFR 161-35, JULY 73)

IDENTIFICATION:

10

EQUAL TIME CONTOURS (MINUTES)

V-51R EAR PLUGS

NOISE SOURCE/SUBJECT:

OPERATION:

MILITARY PLUS AFTERBURNER

SINGLE ENGINE

FREE FLOW

METEOROLOGY:

TEMP = 15 C

BAR PRESS = .760 M HG

REL HUMID = 70 %

F-111A AIRCRAFT

TF30-P-1 ENGINE

FAR FIELD NOISE


OMEGA 1.4

TEST 75-002-036

RUN 03

07 MAY 75


PAGE 10



	MIN	POINT
0	960	A
10	480	B
20	240	C
30	120	D
	60	E
	30	F
	15	G


	(-	-	-)	MIN	POINT
0	(.)	A 960	
	(.)	B 480	
10	(.)	C 240	
	(.)	D 120	
20	(.)	E 60	
	(.)	F 30	

(FIGURE: SOUND PRESSURE LEVEL (SPL))
 (11 EQUAL LEVEL CONTOURS (DB))
 (31.5 HZ OCTAVE BAND)
 (NOISE SOURCE/SUBJECT:)
 (F-111A AIRCRAFT)
 (TF30-P-1 ENGINE)
 (FAR FIELD NOISE)
 (OPERATION:)
 (MILITARY POWER)
 (SINGLE ENGINE)
 (FREE FLOW)
 (METEOROLOGY:)
 (TEMP = 15 C)
 (BAR PRESS = .760 M HG)
 (REL HUMID = 70 %)
 (IDENTIFICATION:)
 (OMEGA 1.4)
 (TEST 75-002-036)
 (RUN 01)
 (07 MAY 75)
 (PAGE 18)



A N G L E I N D E G R E E S

(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (63 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (SINGLE ENGINE
 (FAR FIELD NOISE (FREE FLOW
 (METEOROLOGY: (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (IDENTIFICATION: (OMEGA 1.4
 (TEST 75-002-036
 (RUN 01
 (07 MAY 75
 (PAGE 19




```

IDENTIFICATION: )
)
) OMEGA 1.4
) TEST 75-002-036 )

```


1) METEOROLOGY:

TEMP = 15 C
BAR PRESS = .760 M HG
REL HUMID = 70 %

RUN 01

07 MAY 75
PAGE 20

POINT



AZUJW HZ DWGAWWN

IDENTIFICATION:
OMEGA 1.4
TEST 75-002-036

OPERATION:

1) METEOROLOGY:


MILITARY POWER
SINGLE ENGINE
FREE FLOW

TEMP = 15 C
BAR PRESS = .760 M HG
REL HUMID = 70 %

) PAGE 21


POINT

08




DISTANCE FROM SOURCE (METERS)


10





```
( ( FIGURE: SOUND PRESSURE LEVEL {SPL} ) IDENTIFICATION: )
( ( EQUAL LEVEL CONTOURS (DB) ) )
( ( 11 ) OMEGA 1.4 )
( ( 1000 HZ OCTAVE BAND ) TEST 75-002-036 )
( ( NOISE SOURCE/SUBJECT: ) OPERATION: ) METEOROLOGY: ) RUN 01 )
( ( F-111A AIRCRAFT ) MILITARY POWER ) TEMP = 15 C ) )
( ( TF30-P-1 ENGINE ) SINGLE ENGINE ) BAR PRESS = .760 M HG ) )
( ( FAR FIELD NOISE ) FREE FLOW ) REL HUMID = 70 % ) )
( ( ) ) ) PAGE 23 )
```




(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (2000 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (SINGLE ENGINE
 (FAR FIELD NOISE (FREE FLOW
 (METEOROLOGY:
 (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (IDENTIFICATION:
 (OMEGA 1.4
 (TEST 75-002-036
 (RUN 01
 (07 MAY 75
 (PAGE 24



```
(-----)
( FIGURE: SOUND PRESSURE LEVEL (SPL) ) IDENTIFICATION: )
( EQUAL LEVEL CONTOURS (DB) ) )
( 11 ) OMEGA 1.4 )
( 4000 HZ OCTAVE BAND ) TEST 75-002-036 )
( NOISE SOURCE/SUBJECT: ) METEOROLOGY: ) RUN 01 )
( ( OPERATION: ) TEMP = 15 C ) )
( F-111A AIRCRAFT ) MILITARY POWER ) BAR PRESS = .760 M HG )
( TF30-P-1 ENGINE ) SINGLE ENGINE ) REL HUMID = 70 % )
( FAR FIELD NOISE ) FREE FLOW ) PAGE 25 )
(-----)
```



(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (EQUAL LEVEL CONTOURS (DB)
 (8000 HZ OCTAVE BAND
 (11
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (SINGLE ENGINE
 (FAR FIELD NOISE (FREE FLOW
 (NOISE SOURCE/SUBJECT: (METEOROLOGY:
 (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (07 MAY 75
 (PAGE 26
 (IDENTIFICATION:
 (OMEGA 1.4
 (TEST 75-002-036
 (RUN 01




IDENTIFICATION: OMEGA 1.4
 TEST 75-002-036
 RUN 02
 07 MAY 75
 PAGE 18

METEOROLOGY:
 TEMP = 15 C
 BAR PRESS = .760 M HG
 REL HUMID = 70 %

OPERATION:
 MILITARY POWER
 BOTH ENGINES
 FREE FLOW

NOISE SOURCE/SUBJECT:
 F-111A AIRCRAFT
 TF30-P-1 ENGINE
 FAR FIELD NOISE



(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (63 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT:
 ((OPERATION:
 ((F-111A AIRCRAFT
 ((TF30-P-1 ENGINE
 ((FAR FIELD NOISE
 ((METEOROLOGY:
 ((TEMP = 15 C
 ((BAR PRESS = .760 M HG
 ((REL HUMID = 70 %
 ((MILITARY POWER
 ((BOTH ENGINES
 ((FREE FLOW
 ((OMEGA 1.4
 (TEST 75-002-036
 (RUN 02
 (07 MAY 75
 (PAGE 19
 (IDENTIFICATION:
 ()







FIGURE	SOUND PRESSURE LEVEL EQUAL LEVEL CONTOURS (DB)	IDENTIFICATION
11	125 HZ OCTAVE BAND	OMEGA 1.4
		TEST 75-002-036
		RUN 02
NOISE SOURCE/SUBJECT	OPERATION	METEOROLOGY
F-111A AIRCRAFT	MILITARY POWER	TEMP = 15 C
TF30-P-1 ENGINE	BOTH ENGINES	BAR PRESS = .760 M HG
FAR FIELD NOISE	FREE FLOW	REL HUMID = 70 %
		PAGE 20




(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (250 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (BOTH ENGINES
 (FAR FIELD NOISE (FREE FLOW
 (METEOROLOGY:
 (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (IDENTIFICATION:
 (OMEGA 1.4
 (TEST 75-002-036
 (RUN 02
 (07 MAY 75
 (PAGE 21




(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (500 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (BOTH ENGINES
 (FAR FIELD NOISE (FREE FLOW
 (METEOROLOGY: (TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (IDENTIFICATION: (OMEGA 1.4
 (TEST 75-002-036
 (RUN 02
 (07 MAY 75
 (PAGE 22



(FIGURE: SOUND PRESSURE LEVEL (SPL))
 (EQUAL LEVEL CONTOURS (DB))
 (11 1000 HZ OCTAVE BAND)
 (NOISE SOURCE/SUBJECT:)
 (OPERATION:)
 (F-111A AIRCRAFT)
 (TF30-P-1 ENGINE)
 (FAR FIELD NOISE)
 (METEOROLOGY:)
 (TEMP = 15 C)
 (BAR PRESS = .760 M HG)
 (REL HUMID = 70 %)
 (IDENTIFICATION:)
 (OMEGA 1.4)
 (TEST 75-002-036)
 (RUN 02)
 (07 MAY 75)
 (PAGE 23)




(FIGURE: SOUND PRESSURE LEVEL (SPL))
 (11 EQUAL LEVEL CONTOURS (DB))
 (2000 HZ OCTAVE BAND)
 (NOISE SOURCE/SUBJECT:)
 (F-111A AIRCRAFT)
 (TF30-P-1 ENGINE)
 (FAR FIELD NOISE)
 (OPERATION:)
 (MILITARY POWER)
 (BOTH ENGINES)
 (FREE FLOW)
 (METEOROLOGY:)
 (TEMP = 15 C)
 (BAR PRESS = .760 M HG)
 (REL HUMID = 70 %)
 (IDENTIFICATION:)
 (OMEGA 1.4)
 (TEST 75-002-036)
 (RUN 02)
 (07 MAY 75)
 (PAGE 24)




A N G L E I N D E G R E E S

```
( { FIGURE: SOUND PRESSURE LEVEL {SPL} ) IDENTIFICATIONS )
( { EQUAL LEVEL CONTOURS (DB) ) )
( { 11 ) OMEGA 1.4 )
( { 4000 HZ OCTAVE BAND ) TEST 75-002-036 )
( { NOISE SOURCE/SUBJECT: ) METEOROLOGY: ) RUN 02 )
( { ) TEMP = 15 C ) )
( { F-111A AIRCRAFT ) MILITARY POWER ) 07 MAY 75 )
( { TF30-P-1 ENGINE ) BOTH ENGINES ) )
( { FAR FIELD NOISE ) FREE FLOW ) PAGE 25 )
```




(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (8000 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY POWER
 (TF30-P-1 ENGINE (BOTH ENGINES
 (FAR FIELD NOISE (FREE FLOW
 (METEOROLOGY: TEMP = 15 C
 (BAR PRESS = .760 M HG
 (REL HUMID = 70 %
 (IDENTIFICATION: OMEGA 1.4
 (TEST 75-002-036
 (RUN 02
 (07 MAY 75
 (PAGE 26



ANGLE IN DEGREES

5 6 8 1 1.5 2 3 4 5 6 8 1000
 100
 DISTANCE FROM SOURCE (METERS)

(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (EQUAL LEVEL CONTOURS (DB)
 (63 HZ OCTAVE BAND
 (11
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (MILITARY PLUS AFTERBURNER)
 (TF30-P-1 ENGINE (SINGLE ENGINE)
 (FAR FIELD NOISE (FREE FLOW)
 (METEOROLOGY:)
 (TEMP = 15 C)
 (BAR PRESS = .760 M HG)
 (REL HUMID = 70 %)
 (IDENTIFICATION:)
 (OMEGA 1.4)
 (TEST 75-002-C36)
 (RUN 03)
 (07 MAY 75)
 (PAGE 19)



A N G L E I N D E G R E E S

IDENTIFICATION:
OMEGA 1.4


OMEGA 1.4

1) METEOROLOGY:


0
0
0
1
0
0

REL HUMID = 70 %

PAGE 20




(FIGURE: SOUND PRESSURE LEVEL (SPL)
 (11 EQUAL LEVEL CONTOURS (DB)
 (250 HZ OCTAVE BAND
 (NOISE SOURCE/SUBJECT: (OPERATION:
 (F-111A AIRCRAFT (TEMP = 15 C
 (TF30-P-1 ENGINE (MILITARY PLUS AFTERBURNER (BAR PRESS = .760 M HG
 (FAR FIELD NOISE (SINGLE ENGINE (REL HUMID = 70 %
 ((FREE FLOW)
 (IDENTIFICATION:
 (OMEGA 1.4
 (TEST 75-002-036
 (RUN 03
 (07 MAY 75
 (PAGE 21




DISTANCE FROM SOURCE (METERS)

IDENTIFICATION:
 OMEGA 1.4
 TEST 75-002-036
 RUN 03
 METEOROLOGY:
 TEMP = 15 C
 BAR PRESS = .760 M HG
 REL HUMID = 70 %
 OPERATION:
 MILITARY PLUS AFTERBURNER
 SINGLE ENGINE
 FREE FLOW
 NOISE SOURCE/SUBJECT:
 F-111A AIRCRAFT
 TF30-P-1 ENGINE
 FAR FIELD NOISE




PAGE 23






DISTANCE FROM SOURCE (METERS)

FIGURE: SOUND PRESSURE LEVEL (SPL)
 EQUAL LEVEL CONTOURS (DB)
 11 4000 HZ OCTAVE BAND
 NOISE SOURCE/SUBJECT: (OPERATION:) METEOROLOGY: = 15 C
 F-111A AIRCRAFT (MILITARY PLUS AFTERBURNER) BAR PRESS = .760 M HG
 TF30-P-1 ENGINE (SINGLE ENGINE) REL HUMID = 70 %
 FAR FIELD NOISE (FREE FLOW) PAGE 25



(FIGURE: SOUND PRESSURE LEVEL (SPL))
 (11 EQUAL LEVEL CONTOURS (DB))
 (8000 HZ OCTAVE BAND)
 (NOISE SOURCE/SUBJECT:)
 (F-111A AIRCRAFT)
 (TF30-P-1 ENGINE)
 (FAR FIELD NOISE)
 (OPERATION:)
 (MILITARY PLUS AFTERBURNER)
 (SINGLE ENGINE)
 (FREE FLOW)
 (METEOROLOGY:)
 (TEMP = 15 C)
 (BAR PRESS = .760 M HG)
 (REL HUMID = 70 %)
 (IDENTIFICATION:)
 (OMEGA 1.4)
 (TEST 75-002-036)
 (RUN 03)
 (07 MAY 75)
 (PAGE 26)



A N G L E I N D E G R E E S